

2/PRTS.

10/539839

Attorney Docket: 3926.163

Patent Application

JC05 Rec'd PCT/PTO 20 JUN 2005

AREA OF REPRESENTATION IN AN AUTOMOTIVE NIGHT VISION SYSTEM

BACKGROUND OF THE INVENTION

Field of the invention

[0002] The invention relates to a method for detecting surroundings by means of an automotive night vision system comprising a number of areas.

Related Art of the Invention

[0003] There are already first commercially available driver-assistance systems that improve the visibility for the driver in the event of poor weather or in the dark. These are night vision systems in which an infrared sensor is used to detect the vehicle surroundings ahead. The detected data relating to the surroundings are processed with the aid of a data processing unit to form an image, and are represented for the driver on an optical display in the vehicle. In which case, the driver looks at the optical display in order to pick up information and, if appropriate, can detect dangerous traffic situations.

[0004] IEEE Computer Graphics and Applications, September/October, 1999, page 6: "Night Vision: Infrared Takes to the Road" presents an automotive night vision system that comprises an infrared camera and a head-up display. In which case, the head-up display is used to project the data relating to the surroundings, which are detected by means of the infrared camera and are ahead of the vehicle, onto the windshield in a virtual fashion. In which case, the system lends the driver the possibility of a visual range that is three to five times greater than the visual range typical with a low beam. The result of this is that at a vehicle speed of 60 miles

"EXPRESS MAIL" LABEL NO.: 6155057978045
I HEREBY CERTIFY THAT THIS PAPER IS BEING DEPOSITED WITH THE
UNITED STATES POSTAL SERVICE "EXPRESS MAIL POST OFFICE TO
ADDRESSEE" SERVICE UNDER 37 CFR 1.10 IN AN ENVELOPE ADDRESSED
TO: THE COMMISSIONER OF PATENTS, P.O. BOX 1450, ALEXANDRIA, VA
22313-1450, ON THIS DATE. THE COMMISSIONER IS HEREBY AUTHORIZED
TO CHARGE ANY FEES ARISING HEREFROM AT ANY TIME TO DEPOSIT
ACCOUNT 16-0877.

6/20/05
DATE

SIGNATURE

per hour the maximum reaction time on low beam of 3.5 seconds is raised to a reaction time of 17.5 seconds with night vision.

[0005] A system for assisting driver vision during night driving is presented on the Toyota Motor Corporation website (www.toyota.co.jp/Showroom/All_toyota_lineup/LandCruiserCygnus/safety/index.html). In this case, a camera that is sensitive in the near infrared detects the surroundings and displays them to the driver on a head-up display. On low beam, the system indicates the course of the road, which is ahead of the vehicle light cone and is difficult to recognize, as well as persons, vehicles and obstacles located in the surroundings. To this end, the light cone of the low beam is adjoined by an area that can be recognized with the aid of the night vision system. The area that can be evaluated is ideally situated at approximately 100 m and reaches at most up to approximately 150 m. The system serves, in particular, as an assistant for long-range vision in situations where it is not possible to drive on high beam. When the driver is driving on high beam, the system provides him with information lying ahead by imaging objects which are difficult to recognize in direct view. Through the use of near infrared rays, the system can display the state of the road, objects that have fallen onto the road and other information relating to the road. The high beam light cone, which is specified with a range of approximately 180 m, is adjoined for this purpose by the area that can be detected with the aid of the night vision system. The area that can be detected is at approximately 200 m and is specified as approximately 250 m, at most. All previously commercially available night vision systems are designed in such a way that they can display objects as far

removed as possible. However, they involve the high risk that in situations of poor visibility or in the darkness the driver will be led to drive faster than is possible without a night vision system.

SUMMARY OF THE INVENTION

[0006] It is therefore the object of the invention to provide a method for detecting surroundings by means of an automotive night vision system, with the aid of which information relating to the surroundings ahead is displayed to the driver without, in the process, leading to flying blind.

[0007] The object is achieved according to the invention by means of a method having the features of patent claim 1. Advantageous refinements and developments of the invention are indicated in the dependent claims.

[0008] In accordance with the invention, a method is provided for detecting surroundings by means of an automotive night vision system. In order to detect data relating to the surroundings, the system comprises a number of areas. These include a detection area, wherein the night vision system is sensitive to optical radiation of invisible IR wavelengths, and data relating to the surroundings are detected. The system also comprises an area of representation, the data relating to the surroundings detected therein with the aid of the night vision system being represented for the driver on an optical display. In a way according to the invention, the area of representation of the night vision system in this case comprises at most the light cone of the vehicle high beam area. Because of the restriction of the area of representation, the display shows the driver only those data

relating to the surroundings that he would see in any case on activation of the conventional high beam.

[0009] In a particularly advantageous way, the system comprises an evaluation area within which the data relating to the surroundings detected by means of the night vision system are subjected to evaluation, in particular object recognition.

[00010] In a further advantageous way, a tolerance area adjoins the area of representation of the night vision system. In which case, those data relating to the surroundings which covers the tolerance area are likewise represented for the driver by means of the optical display. In one embodiment of the invention, it is provided that the tolerance area is permanently prescribed. In which case, a tolerance area is advantageous, on the one hand, because no sharp separating line exists between the high beam area and the detection area. On the other hand, the boundary of the high beam area cannot be fixed with sufficient accuracy, because of the angular ranges of the camera, each pixel corresponding to a spatial direction. However, it is also conceivable to control the tolerance area automatically on the basis of further vehicle variables or variables of the surroundings, for example the driving speed. In a particularly preferred embodiment of the invention, the tolerance area is, however, set as a function of the evaluation of the data relating to the surroundings. For example, the tolerance area is automatically expanded whenever an object is situated only partially in the current area of representation. The tolerance area is expanded in this case in such a way that an object is covered completely by the area of representation and the

tolerance area.

[00011] In the driving direction of the vehicle, the area of representation comprises at least a part of the low beam area. In which case, it is preferred not to represent objects in the area directly in front of the vehicle, since the driver can see these objects even without a night vision system. The area of representation is not necessarily laterally bounded in this case. In which case the opening angle of the night vision system is preferably selected in such a way that it does not penetrate the lobe of the high beam area at the side.

[00012] The evaluation area of the night vision system is advantageously designed in such a way that it comprises at least the high beam area of the vehicle. For the purpose of evaluation, the data relating to the surroundings detected in the evaluation area are then subjected to object recognition by means of a data processing unit in conjunction with methods for image processing and classification. If the objects recognized are located only partially in the evaluation area, the evaluation area is automatically expanded in an advantageous way. For this purpose, it is possible to establish, for example, whether a closed object contour is present. The evaluation area is expanded in this case until an object has been completely evaluated. In a particularly advantageous way, however, the evaluation area is designed such that it comprises the entire detection area of the night vision system, it thereby being possible also to detect objects located at a long distance. It is also conceivable in a profitable way not to recognize those objects that are located directly in front of the vehicle, in order to save computing time in the

evaluation.

[00013] In a profitable embodiment of the invention, the objects detected by means of the evaluation in the area of representation are emphasized in the representation. It is preferable for this purpose to color the objects. In which case it is advantageous to subject the detected objects in advance to a classification and subsequently to color them differently with the aid of their class membership (for example, pedestrians, vehicles, ...). It would also be conceivable to represent only the object contour and color this in correspondingly.

[00014] In a further profitable embodiment of the invention, the information relating to the objects detected during the evaluation in the evaluation area is made available to internal vehicle systems for further evaluation. The information can serve the purpose in this case, for example, of activating safety-relevant systems at an early stage, or preparing them to be activated.

[00015] Further features and advantages of the invention emerge from the following descriptions of exemplary embodiments with the aid of the figures. In which case the figures do not show all the possible variants of the invention, further variants advantageously resulting, in particular, from combination.

Brief Description of the Drawings

[00016] In the drawing:

figure 1 shows the area of representation of the night vision

system, which completely comprises the low beam and high beam areas,

figure 2 shows the area of representation of the night vision system, which comprises the high beam area and a lateral tolerance areas,

figure 3 shows the area of representation of the night vision system which partially comprises the low beam and high beam areas, and

figure 4 shows the area of representation of the night vision system, which comprises the high beam area and an additional tolerance area in the driving direction.

Detailed Description of the Invention

[00017] The area of representation of the automotive night vision system (4) according to the invention is illustrated by way of example in figure 1. Here, the area of representation (illustrated in a singly hatched fashion) comprises the low beam area (1) and the high beam area (2) completely. In which case the area of representation extends in the driving direction up to the boundary between the high beam area (2) and the detection area (3).

[00018] Figure 2 shows the area of representation of the automotive night vision system (4), there being no lateral limitation of the high beam area (2), in this case by comparison with the area of representation shown in figure 1. The opening angle of the camera is selected in such a way that tolerance

areas (illustrated in a doubly hatched fashion) adjoin the high beam area (2) at the side.

[00019] The night vision system (4) is designed in figure 3 in such a way that the area of representation differs by comparison with the area of representation shown in figure 1 in that the area of representation in figure 3 preferably comprises only a part of the low beam area (1). In addition, here, the tolerance area is limited at the side, the opening angle of the night vision system (4) being selected in such a way that it does not penetrate the lobe of the high beam area.

[00020] Figure 4 shows by way of example a further variant of the area of representation, the latter having a larger tolerance area by comparison with the area of representation specified in figure 3. The area of representation therefore does not end at the boundary between the high beam area (2) and the detection area (3) but extends further in the driving direction into the detection area (3).